



# Power Steering Stop Leak

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830  
Issue date: 10/22/2015 Revision date: 4/5/2022 Supersedes version of: 8/28/2017 Version: 1.2

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
Name : Power Steering Stop Leak  
Product code : 1755  
Article number : 1755B

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1. Relevant identified uses

Industrial/Professional use spec : Consumer use  
Professional use.  
Function or use category : Lubricants and additives

##### 1.2.2. Uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

BARDAHL NL - OCD NEDERLAND BV  
Maxwellstraat 41  
3316 GP Dordrecht  
Nederland  
T 0031 78 651 2322 - F 0031 78 617 4848  
[mjkooijman@bardahl.nl](mailto:mjkooijman@bardahl.nl) - [www.bardahl.nl](http://www.bardahl.nl)

#### 1.4. Emergency telephone number

Emergency number : +31 (0) 6 54924171  
During office hours: 8.30 t/m 17:00 h

Country	Official advisory body	Address	Emergency number	Comment
	Guy's & St Thomas' Poisons Unit Medical Toxicology Unit, Guy's & St Thomas' Hospital Trust	Avonley Road SE14 5ER London	0870 243 2241	
Ireland	National Poisons Information Centre Beaumont Hospital	PO Box 1297 Beaumont Road 9 Dublin	+353 1 809 2566 (Healthcare professionals- 24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7)	
Israel	Israel Poison Information Center Rambam Health Care Campus	6 Ha'Aliya Street 31096 Haifa	+972 4 854 1900	
Malta	Medicines & Poisons Info Office	Mater Dei Hospital MSD 2090 Msida	+356 2545 6508	
United Kingdom	National Poisons Information Service (Birmingham Centre) City Hospital	Dudley Road B18 7QH Birmingham	0344 892 0111	Only for healthcare professionals
United Kingdom	National Poisons Information Service (Belfast Centre) Royal Victoria Hospital	Grosvenor Road BT12 6BA Belfast	0344 892 0111	Only for healthcare professionals

# Power Steering Stop Leak

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Hazardous to the aquatic environment — Chronic Hazard, Category 3 H412

Full text of H- and EUH-statements: see section 16

##### Adverse physicochemical, human health and environmental effects

No additional information available

#### 2.2. Label elements

##### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Signal word (CLP) : -

Hazard statements (CLP) : H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements (CLP) : P101 - If medical advice is needed, have product container or label at hand.  
P102 - Keep out of reach of children.  
P273 - Avoid release to the environment.  
P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.  
P501 - Dispose of contents and container to a hazardous or special waste collection point.

EUH-statements : EUH208 - Contains 1- (tert-dodecyl thiol) propan-2-ol, Benzene, polypropene derivatives, sulfonated, calcium salts, Ethanol, 2,2'-iminobis-, N-talk-alkylderivaten. May produce an allergic reaction.

#### 2.3. Other hazards

No additional information available

### SECTION 3: Composition/information on ingredients

#### 3.1. Substances

Not applicable

#### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Distillates (petroleum), solvent-dewaxed heavy paraffinic (Note L)	CAS-No.: 64742-65-0 EC-No.: 265-169-7 REACH-no: 01-2119471299-27	50 – 80	Carc. 1A, H350
(2-methoxymethylethoxy)propanol	CAS-No.: 34590-94-8 EC-No.: 252-104-2 REACH-no: 01-2119450011-60	< 5	Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335
1- (tert-dodecyl thiol) propan-2-ol	CAS-No.: 67124-09-8 EC-No.: 266-582-5 REACH-no: 01-2119953277-30	< 1	Skin Sens. 1, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Benzene, polypropene derivatives, sulfonated, calcium salts	CAS-No.: -- EC-No.: -- REACH-no: 01-2120040541-70	< 1	Skin Sens. 1B, H317

# Power Steering Stop Leak

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Ethanol, 2,2'-iminobis-, N-talk-alkylderivaten	CAS-No.: 61791-44-4 EC-No.: 263-177-5	< 0.5	Acute Tox. 4 (Oral), H302 Skin Corr. 1B, H314 Skin Sens. 1A, H317 Asp. Tox. 1, H304 Aquatic Chronic 3, H412
toluene	CAS-No.: 108-88-3 EC-No.: 203-625-9 EC Index-No.: 601-021-00-3 REACH-no: 01-2119471310-51	< 0.5	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361d STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304

Note L: The harmonised classification as a carcinogen applies unless it can be shown that the substance contains less than 3 % of dimethyl sulphoxide extract as measured by IP 346 ("Determination of polycyclic aromatics in unused lubricating base oils and asphaltene free petroleum fractions – Dimethyl sulphoxide extraction refractive index method" Institute of Petroleum, London), in which case a classification in accordance with Title II of this Regulation shall be performed also for that hazard class.

Full text of H- and EUH-statements: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. If medical advice is needed, have product container or label at hand.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Remove contaminated clothing immediately. Wash skin thoroughly with mild soap and water. Wash contaminated clothing before reuse.
First-aid measures after eye contact	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
First-aid measures after ingestion	: Do NOT induce vomiting. Immediately call a POISON CENTER/doctor.

### 4.2. Most important symptoms and effects, both acute and delayed

No additional information available

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media	: Carbon dioxide. Powder. Water haze. Sand.
Unsuitable extinguishing media	: Do not use a heavy water stream.

### 5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire	: Incomplete combustion will generate poisonous carbon monoxide, carbon dioxide and other toxic gases.
--	--

### 5.3. Advice for firefighters

Firefighting instructions	: Exercise caution when fighting any chemical fire. Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting	: Wear self-contained breathing apparatus, rubber boots and thick rubber gloves.

# Power Steering Stop Leak

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Keep public away from danger area. Equip cleanup crew with proper protection. Evacuate area. Ensure adequate ventilation, especially in confined areas.

##### 6.1.1. For non-emergency personnel

No additional information available

##### 6.1.2. For emergency responders

No additional information available

#### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if product enters sewers or public waters. Dam up the liquid spill.

#### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Clean up any spills as soon as possible, using an absorbent material to collect it.

#### 6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". For disposal of solid materials or residues refer to section 13 : "Disposal considerations".

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Precautions for safe handling : Do not eat, drink or smoke when using this product.  
Hygiene measures : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Take off immediately all contaminated clothing.

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a dry, cool and well-ventilated place. Store in original container.  
Incompatible materials : Freezing. heat.

#### 7.3. Specific end use(s)

No additional information available

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### 8.1.1 National occupational exposure and biological limit values

toluene (108-88-3)	
EU - Indicative Occupational Exposure Limit (IOEL)	
IOEL TWA	192 mg/m <sup>3</sup> (Toluene; EU; Time-weighted average exposure limit 8 h; Indicative occupational exposure limit value)
IOEL TWA [ppm]	50 ppm (Toluene; EU; Time-weighted average exposure limit 8 h; Indicative occupational exposure limit value)
IOEL STEL	384 mg/m <sup>3</sup> (Toluene; EU; Short time value; Indicative occupational exposure limit value)
IOEL STEL [ppm]	100 ppm (Toluene; EU; Short time value; Indicative occupational exposure limit value)

# Power Steering Stop Leak

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

<b>toluene (108-88-3)</b>	
<b>Belgium - Occupational Exposure Limits</b>	
OEL TWA	77 mg/m <sup>3</sup> Toluène; Belgium; Time-weighted average exposure limit 8 h)
OEL TWA [ppm]	20 ppm (Toluène; Belgium; Time-weighted average exposure limit 8 h)
OEL STEL	384 mg/m <sup>3</sup> (Toluène; Belgium; Short time value)
OEL STEL [ppm]	100 ppm (Toluène; Belgium; Short time value)
<b>France - Occupational Exposure Limits</b>	
VME (OEL TWA)	76.8 mg/m <sup>3</sup> (Toluène; France; Time-weighted average exposure limit 8 h; VRC: Valeur réglementaire contraignante)
VME (OEL TWA) [ppm]	20 ppm (Toluène; France; Time-weighted average exposure limit 8 h; VRC: Valeur réglementaire contraignante)
VLE (OEL C/STEL)	384 mg/m <sup>3</sup> (Toluène; France; Short time value; VRC: Valeur réglementaire contraignante)
VLE (OEL C/STEL) [ppm]	100 ppm (Toluène; France; Short time value; VRC: Valeur réglementaire contraignante)
<b>Greece - Occupational Exposure Limits</b>	
OEL TWA	192 mg/m <sup>3</sup>
OEL TWA [ppm]	50 ppm
OEL STEL	384 mg/m <sup>3</sup>
OEL STEL [ppm]	100 ppm
<b>Italy - Occupational Exposure Limits</b>	
Local name	Toluene
OEL TWA	192 mg/m <sup>3</sup>
OEL TWA [ppm]	39 ppm
<b>Netherlands - Occupational Exposure Limits</b>	
TGG-8u (OEL TWA)	150 mg/m <sup>3</sup> (Toluene; Netherlands; Time-weighted average exposure limit 8 h; Public occupational exposure limit value)
TGG-8u (OEL TWA) [ppm]	39 ppm (Toluene; Netherlands; Time-weighted average exposure limit 8 h; Public occupational exposure limit value)
TGG-15min (OEL STEL)	384 mg/m <sup>3</sup> (Toluene; Netherlands; Short time value; Public occupational exposure limit value)
TGG-15min (OEL STEL) [ppm]	100 ppm (Toluene; Netherlands; Short time value; Public occupational exposure limit value)
<b>Spain - Occupational Exposure Limits</b>	
Local name	Tolueno
VLA-ED (OEL TWA) [1]	192 mg/m <sup>3</sup>
VLA-ED (OEL TWA) [2]	50 ppm
VLA-EC (OEL STEL)	384 mg/m <sup>3</sup>
VLA-EC (OEL STEL) [ppm]	100 ppm

# Power Steering Stop Leak

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

toluene (108-88-3)	
Remark	Vía dérmica: (Indica que, en las exposiciones a esta sustancia, la aportación por la vía cutánea puede resultar significativa para el contenido corporal total si no se adoptan medidas para prevenir la absorción. En estas situaciones, es aconsejable la utilización del control biológico para poder cuantificar la cantidad global absorbida del contaminante. Para más información véase el Apartado 5 de este documento.), VLB® (Agente químico que tiene Valor Límite Biológico específico en este documento.), VLI (Agente químico para el que la U.E. estableció en su día un valor límite indicativo. Todos estos agentes químicos figuran al menos en una de las directivas de valores límite indicativos publicadas hasta ahora (ver Anexo C. Bibliografía). Los estados miembros disponen de un tiempo fijado en dichas directivas para su transposición a los valores límites de cada país miembro. Una vez adoptados, estos valores tienen la misma validez que el resto de los valores adoptados por el país.), r (Esta sustancia tiene establecidas restricciones a la fabricación, la comercialización o el uso en los términos especificados en el "Reglamento (CE) nº 1907/2006 sobre Registro, Evaluación, Autorización y Restricción de sustancias y preparados químicos" (REACH) de 18 de diciembre de 2006 (DOUE L 369 de 30 de diciembre de 2006). Las restricciones de una sustancia pueden aplicarse a todos los usos o sólo a usos concretos. El anexo XVII del Reglamento REACH contiene la lista de todas las sustancias restringidas y especifica los usos que se han restringido.)
<b>United Kingdom - Occupational Exposure Limits</b>	
WEL TWA (OEL TWA) [1]	191 mg/m <sup>3</sup> Toluene; United Kingdom; Time-weighted average exposure limit 8 h; Workplace exposure limit (EH40/2005)
WEL TWA (OEL TWA) [2]	50 ppm Toluene; United Kingdom; Time-weighted average exposure limit 8 h; Workplace exposure limit (EH40/2005)
WEL STEL (OEL STEL)	384 mg/m <sup>3</sup> Toluene; United Kingdom; Short time value; Workplace exposure limit (EH40/2005)
WEL STEL (OEL STEL) [ppm]	100 ppm Toluene; United Kingdom; Short time value; Workplace exposure limit (EH40/2005)
<b>USA - ACGIH - Occupational Exposure Limits</b>	
Local name	Toluene
ACGIH OEL TWA [ppm]	20 ppm
Remark (ACGIH)	Visual impair; female repro;

### 8.1.2. Recommended monitoring procedures

No additional information available

### 8.1.3. Air contaminants formed

No additional information available

### 8.1.4. DNEL and PNEC

No additional information available

### 8.1.5. Control banding

No additional information available

## 8.2. Exposure controls

### 8.2.1. Appropriate engineering controls

No additional information available

### 8.2.2. Personal protection equipment

**Personal protective equipment:**

Gloves. Protective goggles.

# Power Steering Stop Leak

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### Personal protective equipment symbol(s):



#### 8.2.2.1. Eye and face protection

##### Eye protection:

Use eye protection according to EN 166, designed to protect against liquid splashes.

#### 8.2.2.2. Skin protection

##### Skin and body protection:

Wear suitable protective clothing

##### Hand protection:

In case of repeated or prolonged contact wear gloves. Wear suitable gloves tested to EN374

#### 8.2.2.3. Respiratory protection

##### Respiratory protection:

Ensure good ventilation of the work station

#### 8.2.2.4. Thermal hazards

No additional information available

#### 8.2.3. Environmental exposure controls

No additional information available

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: red.
Odour	: No data available
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: > 100 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: 0.87 – 0.88 (20°C)
Solubility	: Insoluble in water.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

### 9.2. Other information

No additional information available

# Power Steering Stop Leak

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

Stable under normal conditions.

#### 10.2. Chemical stability

Stable under normal conditions.

#### 10.3. Possibility of hazardous reactions

Not established.

#### 10.4. Conditions to avoid

Open flame. Sparks. Heat. Moisture. Freezing.

#### 10.5. Incompatible materials

Water.

#### 10.6. Hazardous decomposition products

Incomplete combustion releases dangerous carbon monoxide, carbon dioxide and other toxic gases.

### SECTION 11: Toxicological information

#### 11.1 Information on toxicological effects

Acute toxicity (oral) : Not classified  
Acute toxicity (dermal) : Not classified  
Acute toxicity (inhalation) : Not classified

#### (2-methoxymethylethoxy)propanol (34590-94-8)

LD50 oral rat	5135 mg/kg
LD50 dermal rat	9500 mg/kg
LD50 dermal rabbit	9500 mg/kg

#### toluene (108-88-3)

LD50 oral rat	> 2000 mg/kg
LD50 dermal rabbit	12223 mg/kg
LC50 Inhalation - Rat	> 20 mg/l/4h

Skin corrosion/irritation : Not classified  
Serious eye damage/irritation : Not classified  
Respiratory or skin sensitisation : Not classified  
Germ cell mutagenicity : Not classified  
Carcinogenicity : Not classified  
Additional information : <3% DMSO (IP346)

#### toluene (108-88-3)

IARC group	3 - Not classifiable
------------	----------------------

Reproductive toxicity : Not classified  
STOT-single exposure : Not classified

#### (2-methoxymethylethoxy)propanol (34590-94-8)

STOT-single exposure	May cause respiratory irritation.
----------------------	-----------------------------------

#### toluene (108-88-3)

STOT-single exposure	May cause drowsiness or dizziness.
----------------------	------------------------------------



# Power Steering Stop Leak

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

STOT-repeated exposure : Not classified

<b>toluene (108-88-3)</b>	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard : Not classified

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : Harmful to aquatic life with long lasting effects.

Hazardous to the aquatic environment, short-term (acute) : Not classified

Hazardous to the aquatic environment, long-term (chronic) : Harmful to aquatic life with long lasting effects.

<b>(2-methoxymethylethoxy)propanol (34590-94-8)</b>	
EC50 - Crustacea [1]	1919 mg/l
Threshold limit - Algae [1]	969 mg/l
Threshold limit - Algae [2]	> 969 mg/l

<b>toluene (108-88-3)</b>	
LC50 - Fish [1]	24 mg/l <i>Salmo gairdneri</i> ( <i>Oncorhynchus mykiss</i> )
LC50 - Fish [2]	13 mg/l <i>Lepomis macrochirus</i>
EC50 - Crustacea [1]	84 mg/l Locomotor effect
EC50 - Crustacea [2]	11.5 – 19.6 mg/l
Threshold limit - Algae [1]	> 400 mg/l <i>Scenedesmus quadricauda</i> ; toxicity test
Threshold limit - Algae [2]	105 mg/l <i>Microcystis aeruginosa</i>

### 12.2. Persistence and degradability

<b>(2-methoxymethylethoxy)propanol (34590-94-8)</b>	
Persistence and degradability	Readily biodegradable.
Biochemical oxygen demand (BOD)	0 g O <sub>2</sub> /g substance
ThOD	2.06 g O <sub>2</sub> /g substance
BOD (% of ThOD)	0 % ThOD

<b>toluene (108-88-3)</b>	
Persistence and degradability	Readily biodegradable.
Biochemical oxygen demand (BOD)	2.15 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	2.52 g O <sub>2</sub> /g substance
ThOD	3.13 g O <sub>2</sub> /g substance
BOD (% of ThOD)	0.69 % ThOD

### 12.3. Bioaccumulative potential

<b>(2-methoxymethylethoxy)propanol (34590-94-8)</b>	
Partition coefficient n-octanol/water (Log Pow)	0.0043
Partition coefficient n-octanol/water (Log Kow)	< 4

# Power Steering Stop Leak

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

toluene (108-88-3)	
BCF - Fish [1]	13.2 Anguilla japonica
BCF - Fish [2]	90 72h; Leuciscus idus
BCF - Other aquatic organisms [1]	380 24h; Chlorella sp; Fresh weight
BCF - Other aquatic organisms [2]	4.2 4.2; Mytilus edulis; Fresh weight
Partition coefficient n-octanol/water (Log Pow)	2.73 Experimental value
Bioaccumulative potential	Low.

### 12.4. Mobility in soil

toluene (108-88-3)	
Surface tension	0.03 N/m (20°C)

### 12.5. Results of PBT and vPvB assessment

No additional information available

### 12.6. Other adverse effects

No additional information available

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

- Product/Packaging disposal recommendations : Collect all waste in suitable and labelled containers and dispose according to local legislation. Prevent entry to sewers and public waters.
- Ecology - waste materials : Avoid release to the environment.

## SECTION 14: Transport information

In accordance with / / ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
<b>14.1. UN number</b>				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
<b>14.2. UN proper shipping name</b>				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
<b>14.3. Transport hazard class(es)</b>				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
<b>14.4. Packing group</b>				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
<b>14.5. Environmental hazards</b>				
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No
No supplementary information available				

# Power Steering Stop Leak

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### 14.6. Special precautions for user

#### Overland transport

No data available

#### Transport by sea

No data available

#### Air transport

No data available

#### Inland waterway transport

No data available

#### Rail transport

No data available

### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

Contains no substance subject to Regulation (EU) 2019/1148 of the European Parliament and of the Council of 20 June 2019 on the marketing and use of explosives precursors.

#### 15.1.2. National regulations

##### France

##### Occupational diseases

Code	Description
RG 4 BIS	Gastrointestinal disorders caused by benzene, toluene, xylenes and all products containing them
RG 84	Conditions caused by liquid organic solvents for professional use: saturated or unsaturated aliphatic or cyclic liquid hydrocarbons and mixtures thereof; liquid halogenated hydrocarbons; nitrated derivatives of aliphatic hydrocarbons; alcohols; glycols, glycol ethers; ketones; aldehydes; aliphatic and cyclic ethers, including tetrahydrofuran; esters; dimethylformamide and dimethylacetamine; acetonitrile and propionitrile; pyridine; dimethylsulfone and dimethylsulfoxide

##### Germany

Water hazard class (WGK)

: WGK 3, Highly hazardous to water (Classification according to AwSV, Annex 1)

Hazardous Incident Ordinance (12. BImSchV)

: Listed in the 12. BImSchV (Annex I) under:

- Quantity threshold for operational area under § 1 para. 1

##### Netherlands

ABM category

: Z(2) - biodegradable substances with hazardous properties for humans and the environment (carcinogenicity/ mutagenicity/reprotoxicity/bioacumulative potential or toxicity)

SZW-lijst van kankerverwekkende stoffen

: Distillates (petroleum), solvent-dewaxed heavy paraffinic, 1- (tert-dodecyl thiol) propan-2-ol, Ethanol, 2,2'-iminobis-, N-talk-alkylderivaten are listed

SZW-lijst van mutagene stoffen

: Distillates (petroleum), solvent-dewaxed heavy paraffinic, 1- (tert-dodecyl thiol) propan-2-ol are listed

# Power Steering Stop Leak

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SZW-lijst van reprotoxische stoffen – Borstvoeding : None of the components are listed  
SZW-lijst van reprotoxische stoffen – Vruchtbaarheid : None of the components are listed  
SZW-lijst van reprotoxische stoffen – Ontwikkeling : toluene is listed

### Denmark

Danish National Regulations : The requirements from the Danish Working Environment Authorities regarding work with carcinogens must be followed during use and disposal  
Danish National Regulations (Additional) : Pregnant/breastfeeding women working with the product must not be in direct contact with the product

### Switzerland

Storage class (LK) : LK 10/12 - Liquids

## 15.2. Chemical safety assessment

No additional information available

## SECTION 16: Other information

### Indication of changes

Section	Changed item	Change	Comments
1.1	Other means of identification	Modified	
1.1	Article number	Removed	
2.2	EUH-statements	Added	
2.2	Precautionary statements (CLP)	Added	
2.2	Hazard statements (CLP)	Added	
3	Composition/information on ingredients	Modified	
6.2	Environmental precautions	Modified	
8.2	Respiratory protection	Modified	
11.1	Additional information	Added	
15.1	Recommendations Danish Regulation (Additional)	Added	

### Abbreviations and acronyms:

Abbreviations and acronyms:

RID: Regulations Concerning the International Transport of Dangerous Goods by Rail

ICAO: International Civil Aviation Organization

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

### Full text of H- and EUH-statements:

Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1

# Power Steering Stop Leak

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Full text of H- and EUH-statements:	
Aquatic Chronic 1	Hazardous to the aquatic environment — Chronic Hazard, Category 1
Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
Carc. 1A	Carcinogenicity, Category 1A
EUH208	Contains 1- (tert-dodecyl thiol) propan-2-ol, Benzene, polypropene derivatives, sulfonated, calcium salts, Ethanol, 2,2'-iminobis-, N-talk-alkylderivaten. May produce an allergic reaction.
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
H225	Highly flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H350	May cause cancer.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
Repr. 2	Reproductive toxicity, Category 2
Skin Corr. 1B	Skin corrosion/irritation, Category 1, Sub-Category 1B
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
Skin Sens. 1A	Skin sensitisation, category 1A
Skin Sens. 1B	Skin sensitisation, category 1B
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.